



### Product Data Sheet – ULTRA SCRATCH TEX (1MM & 2MM)

#### **Description**

Ultra-Scratch Texture is a pre-mixed acrylic based medium profile granular coating supplied in range of tint able bases as well as pre-coloured form. This premium exterior grade product consists of premium water based acrylic emulsion, high grade pigments, fillers, sand, marble and powerful fungicide/ anti-mildew agent. It is available in two Grades.

“1mm” and “2mm”.

#### **Uses**

Ultra-Scratch Texture 1mm and 2mm is a durable sand/marble- based texture coating, ideal for providing an attractive finish coating on correctly prepared exterior & interior wall surfaces of domestic & commercial buildings. Generally, it is trowel applied and finished with a polystyrene float to give scratch swirl, circular or line finish to achieve an even granular appearance high build protective coating, displaying excellent resistance to weathering and excellent exterior durability. It requires to being top coated with Ultratex Membrane for total exterior durability and performance.

#### **Features and Benefits**

- Strong adhesion, Resistance to Mold and Algae
- Excellent flexibility, crack resistance and has good vapour permeability, tint-able to extensive colour range, Easy to apply, Water based.

#### **Suitable Substrates – when properly prepared**

- Cement Render surfaces
- Rendered ACC and Fire cement Sheeting
- Rendered Polystyrene Panels (EPS)
- Rendered Clay and Concrete Brickwork & Block
- Other primed exterior surfaces

#### **Surface preparations**

- Areas not to be coated should be masked and protected.
- All surfaces to be coated must be dry, clean, sound, free from contaminants including oil, mold release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material.

#### **Application**

Mix thoroughly with a power mixer, ensure product colour and consistency before application.

- Generally applied with a steel trowel and finished off with a polystyrene float.  
Apply a skim coat of texture with a steel trowel along the surface; ensure the thickness is limited to the size of scratch texture being used.
- Allow the material to stand for a short time, check if sufficiently dry before "rubbing up" with polystyrene float in a circular or straight line to produce the desired pattern/texture.
- Application must be in a brisk uniform fashion terminating when the whole area is complete, banded by a natural break such as an expansion joint corner etc.
- Let the Texture dry for 24 hours; there after applying one coat of Ultratex Membrane to ensure system durability and performance. Important Information

# ULTRATEX

WALL CLADDING & COATING PTY/LTD



## Product Data Sheet – ULTRA SCRATCH TEX (1MM & 2MM)

### Important Information



Scratch Texture must only be applied in air temperatures between 10°C and 30°C on a dry substrate and must be protected from rain and frost for the first 24 hours or finished work must be protected from rain, frost, and severe weather conditions until fully dried. Avoid application in full sun or hot, windy conditions.

### Safety and Handling

*Refer to Material Safety data sheet and warranty document before use*

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact. Wear protective clothing to minimize skin contact and wear goggles where splatter is likely. Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water. Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

Storage: Store away from food and drink and in a safe place. For further information on *Warranty & Limitations or Material Safety Data Sheet for Ultratex Scratch Texture*, please call (03) 9364 4489 or visit [www.Ultratexvic.com.au](http://www.Ultratexvic.com.au)

Scratch Texture Grade	Packing	Coverage/ Pail	Thk
1 mm	15L Pail	10-12 SQM	Grain Size
2 mm	15L Pail	8-9 SQM	Grain Size
<b>Application Tools</b>	 Steel Trowel / Polystyrene float		
<b>Clean Up</b>	 Clean all with water after use		
<b>Appearance</b>	Coloured gritty viscous liquid paste		
<b>Type</b>	Acrylic copolymer emulsion		
<b>Drying Time (25°C &amp; 50% RH)</b>	Tack Free	Over-coat	Fully Dry
	3Hrs	24hrs	7 days
<b>WFT</b>	Grain Size		
<b>No. of coats</b>	Generally single coat		
<b>Gloss levels</b>	Matt		
<b>Specific Gravity</b>	~ 1.5-1.8		
<b>Thinner</b>	Water – not recommended		
<b>Shelf Life</b>	24 months from date of mfg (sealed)		



1.5 MM



2MM