



## LOW SHEEN ACRYLIC UltrateX Texture painted

### Description

UltrateX Texture painted finish is a 100% acrylic, premium quality, water-based paint. It is easy to apply and has excellent adhesion and durability. Low sheen acrylic can be used on all exterior and interior surfaces, including brick, masonry, timber, and metal. It comes in white, accent, or black base and can be applied using roller, brush, or spray.

A 100% acrylic water thinned paint that dries to a matt finish and is available in white, pastel and deep accent tones. Superior exterior durability—decorates and protects the surface from extreme weather conditions.

### Use

This product has excellent opacity using the lightest fast pigments for exterior use. Suitable on a variety of substrates such as brick, cement render, masonry, plasterboard, metal and timber. Use on all exterior surfaces in the home and on display and feature sign work when a matt finish is required. It may also be used on all interior surfaces.

### Application

Thoroughly stir and apply with brush, roller or spray. Requires two coats for a perfect finish.

### Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

**Timber** – No primer is necessary unless the timber is tannin rich in which case apply Acrylic Wood Primer. Sand and dust down all bare timber and fill holes prior to painting.

**Galvanized Iron and Aluminum** – Remove oil and grease with mineral turpentine. Apply acrylic metal primer.

**Iron and steel** – Remove oil, grease and rust. Treat remaining rust with a rust converter then apply acrylic metal primer.

**Brick and Masonry** – Remove all loose and powdery material with a stiff brush and wash down. No primer required.

**Previously painted** – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Spot prime metal with appropriate primer. When using deep tone colours such as Process Yellow and Vip Red apply a white or light grey undercoat first. This will ensure true colour and help coverage.

### Drying

Under normal drying conditions (above 15° C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C.

### Clean up and thinning

Use clean water only.

### Coverage

14 - 16 square meters per liter per coat

### Pack Size

15 liters

### Colours

Colour card and customer specifications.