

Venetian plaster – decorative tints

PRODUCT AND SUPPLIER

Product name: Venetian Plaster

Use of the substance / preparation: Intended use decorative stucco for internal walls.

SUPPLIER:

Ultratex Wall Cladding & Coating P/L
15A Malcolm Crt,
Kealba, VIC 3021
Tel: 03 9364 4489

HAZARDS

Classification of product Skin Irritation. 2. H315; Eye Irritation. 1 H318

Label Element

Pictograms: Corrosion

Signal Word: DANGER

Hazard Statements: Causes serious eye damage

Causes serious eye damage, Causes skin irritation

IF ON SKIN: Wash with plenty of soap and water. Immediately call a POISON CENTER or doctor/physician

If skin irritation occurs: Get medical advice/attention. Dispose of contents/container in accordance with local regulations. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

DANGER IDENTIFICATION.

RISK OF SERIOUS DAMAGE TO EYES.

COMPOSITION / INFORMATION ON INGREDIENTS

Contains:

Name
Calcium Hydroxide

The complete text of -R- phrases is specified in 'OTHER INFORMATION'.

FIRST AID MEASURES

EYES: Wash immediately with plenty of water for at least 15 minutes and seek medical advice at once.

SKIN: Immediately take out all contaminated clothing and have a shower. Seek medical advice.

INGESTION: Have the patient drink water as much as possible and seek medical advice immediately. Do not induce vomiting before consulting a doctor.

INHALATION: Immediately seek medical advice. In the meantime, remove the patient to open air, far from the contaminated premises; if respiration stops or is difficult, give an artificial respiration adopting the proper measure for the helper.

FIRE-FIGHTING MEASURES

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SUITABLE EXTINGUISHING MEDIA

The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulized water.

EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

None in particular.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc.).

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurized mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear appropriate protective equipment. Send away individuals who are not suitably equipped. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, refer to the other sections of this sheet.

ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighbouring areas. Dilute the product well with water after collection.

METHODS FOR CLEANING UP

Suck the liquid into a suitable container and soak up any leaked product with absorbent inert material (sand, vermiculite, Tripoli powder, universal cement, etc.). Neutralize remaining material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth 'DISPOSAL CONSIDERATION'.

HANDLING AND STORAGE

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure controls

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through elective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION:

Protect hands with work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION:

Wear hood visor or protective visor together with airtight goggles.

SKIN PROTECTION:

Wear professional long-sleeve overalls and safety footwear. Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION:

If the threshold value for one or more of the substances presents in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter. The use of breathing protection equipment, such as masks with organic vapor and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited. If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the



workplace is less than 17% volume, wear self-contained, open - circuit compressed air breathing apparatus or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece. An emergency eye washing and shower system must be provided.

PHYSICAL AND CHEMICAL PROPERTIES

odour	: Lime/slight acrylic
Appearance	: OFF WHITE
Viscosity	: Not available
Vapor density	: Not available
Evaporation Rate	: Not available
Reactive Properties	: Not available
Partition coefficient: n-octanol/water	: Not available
pH	: Alkaline (approx. 12)
Flash point	: Not available
Solubility in water	: Miscible in water
Vapor pressure	: Not available
Specific gravity	: 1.615 - 1700 kg/l

STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

TOXICOLOGICAL INFORMATION

This product may cause serious ocular lesions, cornea opacity, iris lesions, and irreversible eye coloration.

CALCIUM CARBONATE: oral LD50 (mg/kg)
CALCIUM HYDROXIDE: oral LD50 (mg/kg)

ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

DISPOSAL CONSIDERATION

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING: Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

TRANSPORT INFORMATION

This product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road and by Rail, of the International Maritime Dangerous Goods Code and of the International Air Transport Association regulations.

REGULATORY INFORMATION



Xi - Irritant

R 41 - RISK OF SERIOUS DAMAGE TO EYES

S 2 - KEEP OUT OF THE REACH OF CHILDREN

S 25 - AVOID CONTACT WITH EYES

S 26 - IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE

S 39 - WEAR EYE/FACE PROTECTION

S 46 - IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest

OTHER INFORMATION

Text of (R) phrases quoted in section 3 of the sheet.

R 41 - RISK OF SERIOUS DAMAGE TO EYES

Disclaimer

The information contained in the present sheet is based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.